



SCATI VISION RECORDING SERVERS COMPARISON MATRIX

	Product code: VSI-LXU-N04	Product code: VSI-LXU-B01	Product codes: VSI-W10-G508, VSI-LXU-G508	Product codes: VSI-W10-G516, VSI-LXU-G516	Product code: VSI-LXU-K724	Product code: VSK-LXU-SM1	Product code: VSK-LXU-SM2	Product code: VSK-LXU-SM4	Product code: VSK-LXU-SMO-SCSI
Cameras (máx.)	3	4	16	32	64	256	256	256	512
Licenses included	3	4	8	16	32	64	64	128	0
Throughput (máx.)	62Mbps	62 Mbps	279 Mbps	279 Mbps	640 Mbps	1 Gbps	1 Gbps	1 Gbps	2 Gbps
Operating System	Linux	Linux	Windows/Linux	Windows/Linux	Linux	Linux	Linux	Linux	Linux
HDDs qty.	1 (2.5" Surveillance HDD)	1 (3.5" Surveillance HDD)	4 (3.5" Surveillance HDD)	4 (3.5" Surveillance HDD)	8 (3.5" Surveillance HDD)	8 (3.5" SAS Surveillance HDD)	12 (3.5" SAS Surveillance HDD)	24 (3.5" SAS Surveillance HDD)	No internal storage, must use external storage ¹
RAID	NO	NO	NO	NO	YES RAID 0, 1, 5, 10 Hot-swappable Drives	YES RAID 6 configuration Hot-swappable Drives	YES RAID 6 configuration Hot-swappable Drives	YES RAID 6 configuration Hot-swappable Drives	Depending on external storage ¹
Max. Storage	2TB	8TB	40 TB	40 TB	80 TB raw	80 TB raw	120 TB raw	240 TB raw	No internal storage, must use external storage ¹
Automatic Storage management	YES								
Embedded PoE Ports		YES 4 x RJ-45 Gigabit	YES 8 x RJ-45 10/100Mbps	YES 16 x RJ-45 10/100Mbps	YES 24 x RJ-45 10/100Mbps	NO	NO	NO	NO
WAN Interfaces	YES 4 x RJ-45 Gigabit	1 x RJ-45 Gigabit	2 x RJ-45 10/100/1000Mbps	2 x RJ-45 10/100/1000Mbps	4 x RJ-45 10/100/1000Mbps	2 x RJ-45 Gigabit	4 x RJ-45 Gigabit	4 x RJ-45 Gigabit	2 x RJ-45 10GbE ports 2 x RJ-45 Gigabit Ethernet LAN ports 2 x 10 GB 2 port PCI-E (RJ45) additional network card
Autodiagnosis	Embedded monitoring tools of health status								
ONVIF	YES								
I/O Onboard	NO Up to 20/20 via external module	16/16 Expandable up to 20/20 via external module	16/4 Expandable up to 20/20 via external module	16/4 Expandable up to 20/20 via external module	4/4 Expandable up to 20/20 via external module	NO Up to 20/20 via external module	NO Up to 20/20 via external module	NO Up to 20/20 via external module	NO Up to 20/20 via external module
Audio	Bidirectional								
Alarms	YES								
Analytics	Motion detection, Tampering, Object Removed/Added and all analytics included in SCATI EYE Cameras ²	Motion detection, Tampering, Object Removed/Added and all analytics included in SCATI EYE Cameras ²	Motion detection, Tampering, Object Removed/Added and all analytics included in SCATI EYE Cameras ²	Motion detection, Tampering, Object Removed/Added and all analytics included in SCATI EYE Cameras ²	Motion detection, Tampering, Object Removed/Added and all analytics included in SCATI EYE Cameras ²	Motion detection, Tampering, Object Removed/Added and all analytics included in SCATI EYE Cameras ²	Motion detection, Tampering, Object Removed/Added and all analytics included in SCATI EYE Cameras ²	Motion detection, Tampering, Object Removed/Added and all analytics included in SCATI EYE Cameras ²	Motion detection, Tampering, Object Removed/Added and all analytics included in SCATI EYE Cameras ²
Electrical	12VDC	9-36 VDC	100-240VAC	100-240VAC	100-240VAC	100-240VAC 740 W redundant high-efficiency (94 %) power supply with PMBus	100-240VAC 920 W redundant high-efficiency (94 %) power supply with PMBus	100-240VAC 1280 W redundant high-efficiency (94 %) power supply with PMBus	(1 + 1) Redundant high-efficiency (94%) power supply 700W: 100 - 140 V AC, 50 - 60 Hz 750W: 180 - 240 V AC, 60 - 50 Hz
Dimensions & Weight	53x187x111mm 1Kg	70,5x237x164mm 2,3Kg	440 x 400 x 67 mm (1.5U full rack) ≤ 5 Kg	440 x 400 x 67 mm (1.5U full rack) ≤ 5 Kg	428 x 435 x 88 mm (2U full rack) 7.5 Kg (without HDDs)	437 x 648 x 89 mm (2U rack mount) 23.6 Kg (without HDDs)	437 x 648 x 89 mm (2U rack mount) 20.9 Kg (without HDDs)	437 x 660 x 178 mm (4U rack mount) 34 Kg	437 x 705 x 43 mm (1U rack mount) 34 Kg
Certifications	FCC, CE, RoHS	FCC, CE	FCC, CE, RoHS						
NDAA Compliant	YES	YES	NO	NO	YES	YES	YES	YES	YES
Others						Not supported external SAS storage units	Up to 3 external SAS storage units Max. 552 TB raw storage per block	Up to 3 external SAS storage units Max. 672 TB raw storage per block	² External storage (4U): 1) ST-iSCSI (main chassis): RAID 6 / 144TB raw 2) ST-iSAS (secondary chassis): No RAID / 144TB raw

² Features may vary depending on the features of camera model